



Cross recession type Z, size 1  
Penetration depth 1,1-1,35 mm

Directive 2002/95/EC  
"RoHS"  
Compliant

Part no	Dim. L	PCB Thickness	
		min.	max.
<b>CPZS5170X</b>	6,0	1,6	3,0
<b>CPZS5270X</b>	8,0	3,0	5,0
<b>CPZS5370X</b>	10,0	5,0	7,0
<b>CPZS5470X</b>	12,0	7,0	9,0

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.  
OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

finish: Nickel plated				tolerance		
rev.	description	date	name	drawn	date	name
				05.04.06	05.04.06	Schmidt
				appd.		Koch
				norm		
				d-old		

dim. in mm

**CONEC**<sup>®</sup>

scale:	5:1	
material:	Steel	
title:	PAN HEAD TAPPING SCREW used for Advanced TCA with cross recession Z 2,5x6/8/10/12	
dwg no:	Inventor	DIN-A4
	46K1A013	sh: 1
part no:	see table	